



RAINBOW

EMULSION PAINT, MATT

PRODUCT NUMBER	436
TYPE	The high quality emulsion paint based on water-based vinyl copolymer resin with pigment, filler and anti-mildew agent.
USES	Used for indoor cement walls to decoration and protection such as office buildings, hotels, public places, hospitals, shops, houses etc.
CHARACTERISTICS	<ol style="list-style-type: none">1. Meet the national standard CNS 4940.2. Easy application, quick drying, high hiding power and big coating area.3. Excellent water and alkali resistance, meet JIS Z 2911 and JIS Z 2801.4. Special formula design, tough and hard film, good color retention, in particularly washable with water.5. Complete color and soft tone, uniform quality, easy to match with the indoor decoration.
GLOSS	Flat
COLOR	10 colors
HIDING POWER	Above 10.0 m ² /L
MASS DENSITY	Above 1.3 Kg/L
VISCOSITY	90~110 KU (25°C)
DRYING TIME	Set-to-touch 1/2 hr. Dry hard 2 hrs. (25°C)
OPTIMUM FILM THICKNESS	Wet 90 microns Dry 35 microns
THEORETICAL COVERAGE	42.0 m ² /Gal 11.0 m ² /L
OVERCOATING INTERVALS	Min. 4 hrs.
THINNER	Tap water
THINNING RATE	0~15%
PRECEDING COATS	No.410-1 Emulsion Primer
STORAGE SHELF LIFE	Minimum 2 years under normal storage conditions.
APPLICATION METHOD	Spray, Brush, Roller.
NOTE	<ol style="list-style-type: none">1. Before application, stir paint thoroughly, and when paint is too thick, the tap water within specified quantity can be added.2. Adhered moisture, grease, and dirt on substrate must be cleaned thoroughly.3. When color adjustment is required, please use Rainbow water-based color base to avoid color fading.4. New constructed cement walls should wait for at least 2~3 weeks until the moisture content below 12% before application.

EPDM410436XX V1.1

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443