



RAINBOW

WATER-BASED INORGANIC ZINC SILICATE

PRODUCT NUMBER	No.1034
TYPE	A two-pack, inorganic zinc rich rust preventive paint based on ethyl silicate and purity zinc
USES	Long-potent rust preventive coating for ship's shell, cargo hold or steel structures of power oil refineries and pulp factories etc.
CHARACTERISTICS	<ol style="list-style-type: none">1. Excellent corrosion and weather resistance.2. Excellent heat resistance withstands up to 400 .3. Excellent resistance to mechanical damage.4. Unaffected by gas-cutting and welding.5. Excellent resistance to oil and organic solvents.
GLOSS	Flat
COLOR	Gray
WEIGHT	2.8 kg/L (Mixer)
VISCOSITY (25)	70~85 KU (Mixer) (25)
DRYING TIME (25)	Set-to-touch 10mins. Dry hard 1.5 hrs
OPTIMUM FILM THICKNESS	75 μ (microns)
OVERCOATING INTERVALS (25)	Min. 24 hrs.
THEORETICAL COVERAGE	31.4 m ² /Gal 8.3 m ² /L 2.89 m ² /kg
MIXER RATE	= 29 : 71
NON-VOLATILE CONTENT	Above 75% (Mixer)
POT LIFE	7 hrs. (Mixer, 25) 382
THINNER	Water
SUBSEQUENT COATS	
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Airless Spray, Brush.
NOTE	<ol style="list-style-type: none">1. Pour the zinc dust gradually into the base with constant stirring, and then pass through 80mesh filter.2. When used inside tanks, sufficient ventilation must be provided.3. One mist coat must be applied before finish coats to avoid blistering.4. Steel surfaces must be blast-cleaned to SIS Sa2 1/2, with moderate roughness

YUNG CHI PAINT & VARNISH MFG.CO.,LTD

26. YEN HAI 3RD ROAD. KAOHSIUNG, TAIWAN

TEL : 886-7-8713181 FAX : 886-7-8715443