



RAINBOW

WATER-BASED EPOXY CLEAR PRIMER/SEALER

PRODUCT NUMBER	No.1030CP
TYPE	Two pack type clear primer based on water-borne epoxy binder and special hardener.
USES	The primer is suitable for cement wall, cement products, cement board, plasterboard, and concrete wall etc.
CHARACTERISTICS	<ol style="list-style-type: none">1. Excellent resistance to water and alkali.2. Hard film and good adhesion.3. Excellent compatibility with epoxy and PU topcoat.
COLOR	Yellowish clear
S.G.	Above 0.9 kg/L (Mixer)
VISCOSITY (25 °C)	50~65 KU (Mixer) (25 °C)
DRYING TIME (25 °C)	Set-to-touch 4 hrs. Dry hard 12 hrs. Full Cured 7 days
OPTIMUM FILM THICKNESS	Wet 40 μ (microns) Dry 15 μ (microns)
OVERCOATING INTERVALS (25 °C)	Min. 14 hrs. (25 °C)
THEORETICAL COVERAGE	24.6 m ² /L 90.0 m ² /Gal
MIXER RATE	Base : hardener. = 25 : 75
NON-VOLATILE CONTENT	Above 35% (Mixer)
POT LIFE	1.25 hrs. (Mixer, 25 °C)
THINNER	Water
THINNING RATE	0~5% (Excluded cleaning tools)
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Air-spray, Brush.
NOTE	<ol style="list-style-type: none">1. Mix base and hardener according to the mixing ratio and stir thoroughly.2. Adhered moisture, grease, and dirt on substrate must be cleaned thoroughly.3. Avoid applying the paint in rainy weather or humidity above 85% RH, particularly, a wet surface must be thoroughly dried.4. All tools must be cleaned immediately after use.

YUNG CHI PAINT & VARNISH MFG.CO.,LTD

26. YEN HAI 3RD ROAD. KAOHSIUNG, TAIWAN

TEL : 886-7-8713181 FAX : 886-7-8715443