



RAINBOW

GALVANIZED STEEL EMULSION PAINT

NO.	No.500P
TYPE	Emulsion paint for galvanized steel sheets based on special synthetic emulsions, weather resistant pigments, and special adhesive additives.
USES	Primer and topcoat for galvanized steel sheet signboards, roofing, galvanized steel parts, pipes, and truss structures.
CHARACTERISTICS	<ol style="list-style-type: none">1. Strong adhesion to galvanized surfaces without pretreatment.2. Excellent anti-corrosiveness and rust inhibition.3. Excellent resistance to weather and moisture.4. No odor, no pollution.5. Excellent covering power and brush ability.6. Direct application over steel surfaces without rust stains.7. Easy to apply, tools are watering rinsing.
APPLICATION METHOD	Brush, Roller, Airless Spray.
COLOR	White and desired colors.
FINISH	Semi-gloss
SPECIFIC GRAVITY	Above 1.2 kg/L
VISCOSITY (25°C)	60 ~ 90 KU
DRYING TIME (25°C)	Set-to-touch 1 hr. Dry hard 4 hrs.
OVERCOATING INTERVALS (25°C)	Min. 6 hr.
OPTIMUM FILM THICKNESS	Wet 80 microns Dry 30 microns
VOLUME SOLIDS	Above 45%
THEORETICAL COVERAGE	12.5 m ² /L 47 m ² /Gal
THINNER	Fresh water (only for rinsing tools)
PRECEDING COATS	Oleoresins topcoats.
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
NOTE	<ol style="list-style-type: none">1. Before application, stir paint evenly. (Do not thinning)2. Moisture, grease, rust, dirt and loose paints film on substrate must be removed, so are the corrosive salt particles. As a result, paint performance can be ensured.3. Subsequent coat has to wait until paint films of preceding coat completely dry off.4. Avoid applying the paint in rainy weather or humidity above 85% RH, particularly, a wet surface must be thoroughly dried.

YUNG CHI PAINT & VARNISH MFG.CO.,LTD

26. YEN HAI 3RD ROAD. KAOHSIUNG, TAIWAN

TEL : 886-7-8713181 FAX : 886-7-8715443