



RAINBOW

POLYESTER PUTTY

PRODUCT NUMBER	1601
TYPE	The reactive type putty based on polyester resin and special fillers.
USES	Used for mechanical ware, molding parts and car bodies.
CHARACTERISTICS	<ol style="list-style-type: none">1. Very fast drying.2. Good adhesion and flexibility.3. Excellent resistance to humidity, water and corrosion.4. Easy abrasion.5. No volatile solvents contained, paint film won't be shrank.
COLOR	Soil yellow
VISCOSITY	Paste (25)
GRINDING TIME	About 40 minutes
MIXING RATIO	Base : Hardener = 100 : 2 (summer) Base : Hardener = 100 : 3 (winter)
VOLUME SOLIDS	Above 98%
POT LIFE	15 minutes (mixture)
STORAGE SHELF LIFE	Minimum 6 months under normal storage conditions.
APPLICATION METHOD	Manual trawling
NOTES	<ol style="list-style-type: none">1. Adhered moisture, grease, dust and rust on substrate must be cleaned thoroughly.2. Stir base and hardener thoroughly according to the mixing ratio and then apply the mixture immediately because of short pot life.3. Scrape the protrusive putty before drying for the convenience of water mill operation.4. Keep in dark corner to avoid curing.

YUNG CHI PAINT & VARNISH MFG.CO.,LTD

26. YEN HAI 3RD ROAD. KAOHSIUNG, TAIWAN

TEL : 886-7-8713181 FAX : 886-7-8715443