



RAINBOW

MOISTURE-CURED POLYURETHANE PRIMER FOR WATER PROOF

PRODUCT NUMBER	785
TYPE	The one-pack clear coating based on special polyisocyanate resin.
USES	Primer for roofs, balconies, bathrooms, air garden etc, special suitable for cement walls, cement pipes and cement products. Scope of application: cement wall, cement pipelines and cement products.
CHARACTERISTICS	<ol style="list-style-type: none">1. One-pack polyurethane and easy application.2. Can penetrate into cement surface.3. Can be easily coated by the product number 782, 783 and 784.4. Excellent adhesion with cement surface.
COLOR	Clear
SPECIFIC GRAVITY	Above 0.9 Kg/L
VISCOSITY	20 ~ 60 cps (25 °C)
NON-VOLATILE CONTENTS	Above 35%
DRYING TIME	Set-to-touch 1 hr. Dry hard 4 hrs. Fully cured 7 days (25 °C)
OVERCOATING INTERVALS	Min. 1 hr. Max. 3 days (25°C)
OPTIMUM FILM THICKNESS	Wet 100 microns Dry 35 microns
THEORETICAL COVERAGE	8.3 m ² /Kg 0.12 Kg/m ² (Reference amount : Coverage area of per 10 Kg are about 49.5 ~ 66 m ² .)
THINNER	No.736 Polyurethane Thinner (cleaning tools only)
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Brush, Roller
NOTE	<ol style="list-style-type: none">1. Adhered moisture, grease, dust and rust on substrate must be cleaned thoroughly.2. The paint poured out the barrel do not recycle use to ensure quality.

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443