



# RAINBOW

## EPOXY WATERPROOF PRIMER

PRODUCT NUMBER	1062C
TYPE	Two pack, waterproof primer based on epoxy resin, solvent and polyamide resin.
USES	Used for roofs, balconies, bathrooms, air garden etc.
CHARACTERISTICS	<ol style="list-style-type: none"><li>1. Excellent adhesion with cement, wooden products, steel structures, tiles.</li><li>2. Waterproof, leak-proof, preventing cement for chalking and cracking.</li><li>3. Excellent resistance to acids, alkalis, oils, chemicals and water.</li><li>4. Light gray paint film is easy to distinguish and colored on the substrate.</li></ol>
COLOR	Light gray
SPECIFIC GRAVITY	Above 1.3 Kg/L
VISCOSITY	30 ~ 50 KU (25°C)
NON-VOLATILE CONTENTS	Above 50%
DRYING TIME	Set-to-touch 1 hr.      Dry hard 6 hrs.      Fully cured 7 days (25°C)
OVERCOATING INTERVALS	Min. 1 hr.      Max. 3 days (25°C)
OPTIMUM FILM THICKNESS	Wet 100 microns      Dry 60 microns
THEORETICAL COVERAGE	0.2 Kg/m <sup>2</sup> (depending on materials)
PRECEDING COATS	No.782 Golden Blanket Polyurethane For Water Proof No.783 Silver Blanket Polyurethane For Water Proof No.784 Anti-sag Polyurethane For Water Proof No.424 LOCK PROOF® Water-based Waterproof Coating
THINNER	No.1005 Epoxy Thinner or No.807 Xylene (cleaning tools only)
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Brush, roller, spray
NOTE	<ol style="list-style-type: none"><li>1. Adhered moisture, grease, dust and rust on substrate must be cleaned thoroughly.</li><li>2. The paint poured out of barrel do not recycle use to ensure the quality.</li><li>3. Avoid applying paint in the moisture above 85% R.H. or the moisture content of the cement surface more than 12%.</li><li>4. When applying, the hardener must be firstly poured in the mixing barrel then to pour in the base, to avoid uneven mixing.</li><li>5. When applying, the mixture must be used electric mixer to stir thoroughly. The manual stirring is easy to let paint film dry uncompleted.</li><li>6. The paint must storage in ventilation and shade place, so do not place the paint in outdoor to exposure, to avoid effect the quality of paint.</li></ol>

**YUNG CHI PAINT & VARNISH MFG. CO., LTD.**

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.  
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181  
FAX:886-7-8715443