



# RAINBOW

## RAINBOTHERM 520

PRODUCT NUMBER	30520
TYPE	Heat resistant paint based on special resins with aluminium pigment.
CHARACTERISTICS	<ol style="list-style-type: none"><li>1. Heat resisting paint for generators, chimneys and other high temperature in chemical and steel works.</li><li>2. Good heat resistance stand to 200°C.</li><li>3. Good weather resistance.</li><li>4. Good oil and sea water resistance.</li><li>5. Good adhesion.</li><li>6. Easy application.</li></ol>
GLOSS	Gloss
COLORS	Aluminum
VOLATILE ORGANIC COMPOUND CONTENT	VOC 700 (g/l) below
PRODUCT WEIGHT	Above 1.0 kg/L
DRYING TIME	Set-to-touch 2 hrs                      Dry hard 4 hrs (25°C)
OPTIMUM FILM THICKNESS	Dry 25 Micron)
VOLUME SOLID	37±2 %
THEORETICAL COVERAGE	47.3 m <sup>2</sup> /Gal      12.5 m <sup>2</sup> /L
OVERCOATING TABLE	Min. 16 hours
THINNER	No. 1521 Paint Thinner
THINNER RATE	0~2% (by bush and roller)      0~3% (Airless)
RECOMMENDED SPEC.	Please refer the painting specification
SHELF LIFE	Minimum one year under normal storage condition
APPLICATION METHOD	Airless spray, Bush and Roller
NOTE	<ol style="list-style-type: none"><li>1. Adhered water, grease and dust on substrate must be thoroughly clean.</li><li>2. Substrate temperature should be 3°C above dew point, rainy day and relative humidity during application and curing should be below 85%, or job is to be stopped.</li><li>3. Whilst application in the confine space, adequate ventilation must be maintenance.</li></ol>

EPDM3030520X V1.0

# YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.  
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181  
FAX:886-7-8715443