



RAINBOW

RAINBOTHERM 550

PRODUCT NUMBER	30550	
TYPE	Heat resistant paint based on silicone resin with heat-resisting pigment.	
CHARACTERISTICS	<ol style="list-style-type: none"> 1. Heat resisting paint for generators, boilers, chimneys and other high temperature in chemical and steel works. 2. Good heat resistance stand up 500°C. 3. Excellent resistance to oil and water. 4. Good adhesion. 5. Easy application. 	
GLOSS	Gloss	
COLORS	Aluminum	
VOLATILE ORGANIC COMPOUND CONTENT	VOC 700 (g/l) below	
PRODUCT WEIGHT	Above 1.0 kg/L	
DRYING TIME	Set-to-touch 2 hrs	Dry hard 4 hrs (25°C)
OPTIMUM FILM THICKNESS	Dry 25 Micron)	
VOLUME SOLID	25±2 %	
THEORETICAL COVERAGE	10 m ² /Gal 10 m ² /L@ 25µm	
OVERCOATING TABLE	Min. 24 hours	
THINNER	No Thinner should be added	
RECOMMENDED SPEC.	Please refer the painting specification	
SHELF LIFE	Minimum one year under normal storage condition	
APPLICATION METHOD	Airless spray, Bush and Roller	
NOTE	<ol style="list-style-type: none"> 1. Adhered water, grease and dust on substrate must be thoroughly clean. 2. Substrate temperature should be 3°C above dew point, rainy day and relative humidity during application and curing should be below 85%, or job is to be stopped. 3. Whilst application in the confine space, adequate ventilation must be maintenance. 	

EPDM3030550X V1.0

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
 FAX:886-7-8715443