



# RAINBOW

## OIL PRIMER, WHITE

PRODUCT NUMBER	109
TYPE	White primer based on long oil alkyd resin with weather resistant titanium dioxide.
USES	Used for wooden products.
CHARACTERISTICS	<ol style="list-style-type: none"><li>1. Fast drying with good adhesion.</li><li>2. High pigment composition can effectively fill wood gap and pores to prevent the topcoat loss gloss due to absorption of wood.</li><li>3. Easy application.</li></ol>
GLOSS	Below 15%
COLOR	White
HIDING POWER	Above 5 m <sup>2</sup> /L
MASS DENSITY	Above 1.5 Kg/L
VISCOSITY	80~100 KU (25°C)
DRYING TIME	Set-to-touch 1 hr.                      Dry hard 4 hrs. (25°C)
OPTIMUM FILM THICKNESS	Wet 85 microns                      Dry 40 microns
THEORETICAL COVERAGE	44.6 m <sup>2</sup> /Gal                      11.8 m <sup>2</sup> /L                      7.9 m <sup>2</sup> /Kg
OVERCOATING INTERVALS	Min. 10 hrs.                      Max. 6 months
NON-VOLATILE CONTENT	Above 70%
THINNER	NO.805 Paint Thinner (OM-07)
THINNING RATE	5~10% (depends on tools used)
SUBSEQUENT COATS	Rainbow Brand Ready-mixed Paint, Synthetic Enamel.
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Brush
NOTE	<ol style="list-style-type: none"><li>1. Adhered sawdust, grease, dirt on wood substrate must be cleaned thoroughly.</li><li>2. Mix base and thinner rate according to maker's standard and stir thoroughly.</li><li>3. This product is not suitable for anti-corrosive use on the steel.</li></ol>

EPDM010109XX V1.0

# YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.  
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181  
FAX:886-7-8715443