



RAINBOW

WATER BASE MULTIPURPOSE WALL SEALER

PRODUCT NUMBER	429
TYPE	The multipurpose primer based on excellent water and alkali resistant water-based acrylic resin and filler.
USES	Used for exterior cement wall, old solvent-based acrylic paint film or tiles.
CHARACTERISTICS	<ol style="list-style-type: none">1. Very fast drying, easy application.2. Very good penetration with the cement substrate, and very good adhesion with solvent-based, water-based acrylic old paint film and tiles.3. Excellent alkali resistance, for salt damage of new cement wall with has seal function.4. Add anti-mildew agent to inhibit the mold growth in wall.5. Diluting with water, without pollution and fire damage.
GLOSS	Semi-gloss
COLOR	Semi-transparent
MASS DENSITY	Above 1.0 Kg/L
VISCOSITY	65~85 KU (25°C)
DRYING TIME	Set-to-touch 1/2 hr. Dry hard 3 hrs. (25°C)
OPTIMUM FILM THICKNESS	Wet 90 microns Dry 20 microns
THEORETICAL COVERAGE	42.0 m ² /Gal 11.1 m ² /L
OVERCOATING INTERVALS	Min. 4 hrs.
NON-VOLATILE CONTENT	Above 27.0%
THINNER	Tap water
THINNING RATE	0~5%
SUBSEQUENT COATS	No.406, 407, 408, 409, 410, SA2000, SA3000, 433 Emulsion Paint
STORAGE SHELF LIFE	Minimum 2 years under normal storage conditions.
APPLICATION METHOD	Spray, Brush, Roller.
NOTE	<ol style="list-style-type: none">1. Before application, stir paint evenly, and when paint is too thick, the tap water within specified quantity can be added.2. Adhered moisture, grease, and dirt on substrate must be cleaned thoroughly.3. The application must wait for 2 to 3 weeks until the walls were completely dry off and the moisture content under 12%, because the new constructed cement walls contain a lot of moisture and free alkaline substances that may reduce paint film performance and adhesion.

EPDM410429XX V1.0

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443