



RAINBOW

STRIPPABLE VARNISH

PRODUCT NUMBER.	609
TYPE	The strippable varnish based on chlorinated vinyl resin and plasticizer.
USES	Used for machinery, equipment and signs to do temporary maintenance.
CHARACTERISTICS	<ol style="list-style-type: none">1. Very fast drying.2. Dry film is easily whole piece stripped by hand.3. Easy application.
APPEARANCE	Transparent or translucent liquid
MASS DENSITY	Above 0.85 Kg./L
VISCOSITY	55~70 KU (25°C)
DRYING TIME	Set-to-touch 1/2 hr. Dry hard 1 hr. (25°C)
OPTIMAL FILM THICKNESS	Wet 120 microns Dry 35 microns
THEORETICAL COVERAGE	31.4 m ² /Gal 8.30 m ² /L 9.7 m ² /Kg.
VOLUME SOLIDS	Above 30%
THINNER	Appropriate thinner for strippable varnish
THINNER RATE	0~5% (cleaning tools excluded)
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Brush, Spray
NOTES	Adhered moisture, grease, dirt, dust and rust on the substrate must be cleaned thoroughly.

EPDM060609XX V1.0

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443