



RAINBOW

ACRYLIC VARNISH

PRODUCT NUMBER	618
TYPE	The varnish based on acrylic synthetic resin and anti-ultraviolet additive.
USES	Used for colored paint film to protection.
CHARACTERISTICS	<ol style="list-style-type: none">1. Fast drying and smooth paint film.2. High transparency to present original colors.3. Very good weather resistance with good gloss and color retention.4. Hard film with good abrasion resistance.5. Very good adhesion and without glutinosity.6. Very good chemicals and pollution resistance.7. Do not dissolve the lower layer's colored paint film.
APPEARANCE	Transparent liquid
MASS DENSITY	Above 0.85 Kg/L
VISCOSITY	55~65 KU (25°C)
DRYING TIME	Set-to-touch 1/2 hr. Dry hard 4 hrs. (25°C)
OPTIMUM FILM THICKNESS	Wet 50 microns Dry 20 microns
THEORETICAL COVERAGE	75.7 m ² /Gal 20.0 m ² /L 23.5 m ² /Kg
OVERCOATING INTERVALS	Min. 12 hrs.
VOLUME SOLIDS	Above 40%
THINNER	No.805 Paint Thinner (OM-07)
THINNER RATE	5~10% (cleaning tools excluded)
PRECEDING COATS	Rainbow Brand Ready-Mixed Paint, Synthetic Enamel, Color Toner
STORAGE SHELF LIFE	Minimum 2 years under normal storage conditions.
APPLICATION METHOD	Brush, Spray.
NOTE	<ol style="list-style-type: none">1. Please use the specified thinner to dilute.2. Adhered dust, moisture, sawdust or grease on the substrate must be removed thoroughly.3. The standard of painting is 1 to 2 times depending on actual need, and avoid painting to insufficient drying of previous paint coat.

EPDM060618XX V1.0

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443